

#7 Flexible Unit Control

Introduction

The NanoPhotometer® Family offers a unique range of nanovolume and/or cuvette UV/VIS spectrophotometers with flexible control options. All NanoPhotometer® models can be accessed and controlled by a variety of control devices. In addition, a built-in touch screen option is available for independent stand-alone operation.

Stand-Alone Operation

The optional glove compatible color touchscreen converts the NanoPhotometer® into a stand-alone instrument. With the optional battery pack (not available for the N50), mobility and independence from the power grid can be added for at least 10 hours.



Figure 1: Different control devices/options for the NanoPhotometer®

Flexible Unit Control

All NanoPhotometer® models have flexible control device options like Windows/Mac computers, Android/Apple tablets and/or Android/Apple smartphones. Windows computers can either be connected via USB cable, through Ethernet cable within the local network or with a password secured WiFi connection to the unit's own hotspot. For Mac computers, a USB cable connection is required. All portable control devices like tablets and smartphones can be connected via a password secured WiFi connection. The NanoPhotometer® App is available from Google Play and the Apple App Store for free. The apps for Windows and Mac can be found on our website at www.implen.de/downloads.

Portable control devices like tablets and smartphones have the additional benefit to allow data storage on the control device in Excel and/or PDF format.

HDMI

All NanoPhotometer® models are equipped with an HDMI interface to connect an external monitor or projector to present data e.g. for teaching classes.

Keyboard and Mouse

For operation without using the touch capability, the NanoPhotometer® can be controlled via a wired USB mouse and/or a wired USB keyboard (Figure 2).



Figure 2: NanoPhotometer® with mouse for easy operation.

Mouse and keyboard can be used for direct data input or to control the NanoPhotometer® with a monitor or projector connected via HDMI.

NanoPhotometer® Hotspot

All NanoPhotometer® models are equipped with a Wireless Hotspot for secure data access and to control the instrument via a Windows computer, an Android/Apple tablet or an Android/Apple smartphone. The SSID of the Hotspot is the serial number of the instrument.